

# Method and apparatus for wireless communication in a high velocity environment

Bibliographic data	Description	Claims	INPADOC legal status
<b>Publication number:</b>	JP2006512874 (T)		
<b>Publication date:</b>	2006-04-13		
<b>Inventor(s):</b>			<b>Also published as:</b>
<b>Applicant(s):</b>			JP4180603 (B2)
<b>Classification:</b>			US2005020203 (A1)
- <b>international:</b>	H04B1/707; H04L12/56; H04W36/00; H04W36/32; H04B1/707; H04L12/56; H04W36/00		US7558575 (B2)
- <b>European:</b>	H04W36/00; H04B1/707F; H04Q7/38H		WO2005011176 (A2)
<b>Application number:</b>	JP20050518177T 20040709		WO2005011176 (A3)
<b>Priority number(s):</b>	US20030489796P 20030724; US20040872636 20040621; WO2004US22085 20040709		<a href="#">more &gt;&gt;</a>

[View INPADOC patent family](#)

[View list of citing documents](#)

[Report a data error here](#)

Abstract not available for JP 2006512874 (T)

Abstract of corresponding document: **US 2005020203 (A1)**

A communication system transitions from a high velocity mode of operation to a non-high velocity mode of operation based on a movement of a mobile station. When the communication system is in a high velocity mode of operation, the communication system promotes pilots from a High Velocity Neighbor Set of the mobile station or a controller. When the communication system is in a non-high velocity mode of operation, the communication system promotes pilots from a Neighbor Set of the mobile station or the controller. The communication system may further include a high velocity repeater that, when co-located with the mobile station, is capable of providing a communication link between the mobile station and a radio access network servicing the mobile station.

